

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

Noise calculation model:

Danish low frequency 2024

Wind speed (at 10 m height):

6,0 m/s - 8,0 m/s, step 2,0 m/s

Terrain reduction:

-1.5 dB(A) Onshore

-3 dB(A) Offshore

Meteorological coefficient, C0:

Selected option: Fixed value: 0,0 dB

Type of demand in calculation:

1: WTG noise is compared to demand (DK, DE, SE, NL etc.)

Noise values in calculation:

All noise values are mean values (Lwa) (Normal)

Pure tones:

Pure tones penalty is added to total noise impact at receptors

Noise sensitive area

Height above ground level, when no value in NSA object:

1,5 m; Don't allow override of model height with height from NSA object

Uncertainty margin:

0,0 dB; Uncertainty margin in NSA has priority

Deviation from "official" noise demands. Negative is more restrictive, positive is less restrictive.:

0,0 dB(A)

Low frequency calculation

All coordinates are in

Latvian TM LKS92-LKS92 (LV)

WTG: ENERCON E-175 EP5 E2 7000 175.0 !O!

Noise: Mode 00 - OM-0-0 - E-175 EP5 E2 - 7000 (7000 kW)

Source Source/Date Creator Edited
ENERCON GmbH 21.07.2025 EMD 02.07.2025 21:56

The sound power levels do not include uncertainties.

According to manufacturer specification document (D03045913_1.0_de_Technisches Datenblatt_Betriebsmodus OM-0-0 - E-175 EP5 E2 - 7000 kW.pdf/D02887114_2.1_de_Terzbandpegel Betriebsmodus OM-0-0 - E-175 EP5 E2 - 7000 kW.pdf).

Enercon reserves the right to change the above specifications without prior notice.

Status	Low frequency data															
	Hub	Wind	LwA,ref	10,0	12,5	16,0	20,0	25,0	31,5	40,0	50,0	63,0	80,0	100,0	125,0	160,0
	height	speed		Hz	Hz	Hz	Hz	Hz	Hz	Hz	Hz	Hz	Hz	Hz	Hz	Hz
	[m]	[m/s]	[dB(A)]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
Generic data based on turbine power (very uncertain)	162,0	6,0	92,9	50,8	54,5	58,6	62,3	66,2	69,7	74,0	77,6	80,5	82,5	84,4	88,5	87,5
Generic data based on turbine power (very uncertain)	162,0	8,0	95,2	50,2	54,4	59,0	63,2	67,7	71,5	76,1	80,7	83,6	85,8	87,6	90,2	89,5

Noise sensitive area: A Maja 142,3. km

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]

20,0 dB(A) 20,0 dB(A)

No distance demand

dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: B Mizuki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: C Vigriezes

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: D Sunaine

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: E Lejas Sunas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: F Sunu Medilas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: G Maja Nr. 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: H Silini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: I Me ž sunas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: J Kastanis

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: K Sunu Pakalne

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: L Sunu Meijas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: M Veca skola

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: N Kuku Pasile

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: O Kuku stacija

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: P Kuku stacija

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: Q Kuku stacija

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: R Lejas Suni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: S Celinieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: T Podnieki 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: U Papeles

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: V Kuku Pasile 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: W Nesaulu Pasile

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: X Bambari

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: Y Kukas Nr. 32

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: Z Zeltinkukas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AA Kukas Nr. 29

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AB Celmini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AC Celminu Plo š lejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AD Saules

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AE Lukapicku Bajari

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AF Driksnas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AG Lei š u Sils

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AH Silmalas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AI Kunci

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AJ Palejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AK Ozolgravas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AL Purmalrasas 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AM Rozes

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AN Gobinas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AO Kukas Nr. 5A

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AP Kukas Nr. 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AQ Kaplica

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AR Kukas Nr. 8

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AS Kukas Nr. 22

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AT Vasjkova nams

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AU Kukas Nr. 7

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AV Kukas Nr. 28

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AW Kukas Nr. 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AX Biteniek

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AY Me ž a Kunci

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: AZ Kukas Nr. 33

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BA Kukas Nr. 24

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BB Kukas Nr. 27

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BC Kukas Nr. 10

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BD Kukas Nr. 9

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BE Kukas Nr. 3

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BF Skolas iela 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BG Skolas iela 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BH Kuku Drava

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BI Kukas Nr. 17

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BJ Maja 145,3. km

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BK Kukas Nr. 6

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BL Kukas Nr. 23

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BM Kukas Nr. 15

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BN Kukas Nr. 16

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BO Kukas Nr. 31

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BP Dukernieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BQ Lukapickas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BR Purmalrasas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BS Kukas 11

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BT Kukas Nr. 4

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BU Kukas Nr. 34

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BV Kuku Medilas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BW Lejaskastani

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BX Cela posms Kukas-Me ž are 146,034. km

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BY Kraukli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: BZ Kuku Balo ž i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CA Kukas Nr. 13

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CB Kukas Nr. 12

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CC Kartupnieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CD Kukas Nr. 30

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CE Zeltinkukas 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CF Mednieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CG Zallauki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CH O š lejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CI Ilgas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CJ Kraces

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CK Ausekli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CL Kunci 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CM Janci š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CN Kukas Nr. 5

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CO levas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CP Peteri 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CQ Jani š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CR Celavej š

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CS Kukas Nr. 36

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CT Kukas Nr. 20

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CU Speldzinu Ozolini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CV Lauktehnika 18

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CW Smil š kalni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CX Bisenieki 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CY Dujas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: CZ Papolu Kaleji

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DA Me ž amajas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DB Kalna Namiki 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DC Malini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DD Irbes

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DE Lauktehnika 17

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DF Lauktehnika 10

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DG Lauktehnika 8

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DH Lauktehnika 5

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DI Lauktehnika 20

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DJ Lauktehnika 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DK Lauktehnika 6

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DL Lauktehnika 9

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DM Speldzinas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DN Virzinas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DO Lauktehnika 3

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DP Papolu Birzite 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DQ Kalnaspeldzini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DR Stiebrini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DS Zemdegas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DT Lici š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DU Kalna Namiki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DV Birznieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DW Papolu Me ž lejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DX Lauktehnika 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DY Priednieku Bisenieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: DZ Me ž malas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EA Druvina

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EB Bisenieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EC Vainagi

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: ED Kuku Pasile

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EE Aijas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EF Ciruli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EG Sikstuli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EH Sikstuli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EI Priedites

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EJ Martini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EK Akmeni š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EL Lei š u Sils

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EM Lei š usils

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EN Dzila Vada

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EO Strazdi

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EP Radini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EQ Kreslini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: ER Sili

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: ES Skujenieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: ET Salmini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EU Senci

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EV Pakalni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EW Skalbes

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EX Kastani

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EY Kvie š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: EZ Pukulejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FA Celinieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FB Purvini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FC Salenieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FD Me ž a Rasas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FE Dravnieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FF Ogu Purvs

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FG Jaunmedni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FH Graudini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FI Birznieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FJ Me ž a Papuli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FK Noras

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FL Me ž mali

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FM Kurani

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FN Irbites

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FO Ruki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FP Berzkalni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FQ Saulcerini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FR Airites

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FS Lejnieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FT Vipmali

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FU Galvani 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FV Polakas 3

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FW Žagari

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FX Cepli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FY Gu ž ani

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: FZ Perles

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GA Plo š i 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GB Plo š i 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GC Polakas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GD Polakas 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GE Lidijs

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GF Ausekli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GG Ezerkikaukas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GH Kalupnieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GI Kalnvidi

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GJ Celmalas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GK Zemturi

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GL Bukai š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GM Kalna Galvani

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GN Lauri

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GO Roni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GP Roni 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GQ Ziedini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GR Strautini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GS Ozolnieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GT Paegli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GU Sausais Krogs

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GV Druvas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GW Saulkrasti

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GX Jaundruvas 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GY Dzilas 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: GZ Dzilas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HA Zilites

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HB Imanti

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HC Birzes

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HD Avotini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HE Biksti

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HF Tudalinas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HG Kalnares

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HH Polakas 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HI Staltini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HJ Su š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HK Vizbuli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HL Jaundruvas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HM Strautlejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HN Kikaukas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HO Kalnsetas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HP Irgeni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HQ Straumenini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HR Alejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HS Krasta Ozoli

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HT Galvani

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HU Ezerkikaukas 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HV Spuldzeni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HW Bajari

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HX Maurini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HY Vidulejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: HZ Brivares

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IA Mui ž nieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IB Aparnieki

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IC Urgas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: ID Me ž mui ž a

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IE Neretas 2

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IF Neretas 9

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IG Neretas 4

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IH Krastini

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: II Licu Dzirnavas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IJ Strauti

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IK Purenes

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IL Uplejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IM Straumeni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IN Birzmalie š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IO Bazes stacija

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IP Spridi š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IQ Malkalni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IR Lici š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IS Neretas 7

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IT Lejas 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IU Rasas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IV Upenes

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IW Neretas 5

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IX Me ž a Mui ž a

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IY Neretas 6

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: IZ Vilni š i

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JA Raceni

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JB Valodzite

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JC Ievinas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JD Vipes skola

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JE Vipes skola

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JF Vipes skola

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JG Abeles

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JH Vipes skola 1

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JI Vetras

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:
6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JJ Lejas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

DECIBEL - Assumptions for noise calculation

Calculation: Low-Frequency_Enercon E-175 EP5 (Regular dwellings)

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB

Noise sensitive area: JK Me ž setas

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: Use default value from calculation model

No temporal binning

Noise demand:

6,0 [m/s] 8,0 [m/s]
20,0 dB(A) 20,0 dB(A)

No distance demand
dLsigma

10,0 Hz	12,5 Hz	16,0 Hz	20,0 Hz	25,0 Hz	31,5 Hz	40,0 Hz	50,0 Hz	63,0 Hz	80,0 Hz	100,0 Hz	125,0 Hz	160,0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4,9	5,9	4,6	6,6	8,4	10,8	11,4	13,0	16,6	19,7	21,2	20,2	21,2

Pure tone penalty: 0 dB